



Lamp Wastes Management Facility (LWMF) and Extended Producers Responsibility (EPR)

Raquel S. Huliganga



*DEPARTMENT OF ENERGY
PHILIPPINES*




Presentation Outline

2

- Lamp Wastes Management (LWM) in the Philippines
- Implementation of EPR and Operationalization of a LWM Facility (Mercury Recovery)

DOE's Initiative on Lamp Wastes Management

33






LAMP WASTE MANAGEMENT IN THE PHILIPPINES


Evolution of the Lamp Waste Management in the Philippines

5




Evolution of the Lamp Waste Management in the Philippines

6




Lamp Wastes Generation in the Philippines

7



Market Analysis of LWM Services




Finance and Operational Scenario

Market Data: Projected Waste Stream in Tonnage

9

Estimated Waste Stream Philippines (Tonnage)



Implementation of EPR and Operationalization of a LWM facility (Mercury Recovery)

10




What is EPR?

11

“An environmental policy approach where the producers’ responsibility, physical and/or financial, for a product is extended to the post-consumer stage of a product’s life cycle”

- (OECD, 2001)


Proposed EPR Model and the Lighting Products Value Chain




Philippine Lighting Products EPR Model

Critical Role of an Effective LWM Facility

13



Proposed LWM (Mercury Recovery) Facility



Brief Profile of the LWM Facility

15

Parameters	Description
Basic Technology	Mercury recovery technology
Capacity	6 million lamps per year for 8-hour daily operations
Investment Cost	1.3M USD
Source of Fund	Part of PEEP Loan Agreement
Input materials	Busted lamps
Outputs	Glass - 88% Metals - 5% Mercury - 0.005% Powders (with the rare earth) - 3% Others (including resinous materials)- 4%


Brief Profile of the LWM Facility

16

Parameters	Description
Auxiliaries	<ul style="list-style-type: none">• Dehumidifier / Drying oven• Programmable Logic Controller (PLC) System• Continuous mercury analyzer• Two series of connected carbon filters
Power consumption	75 kW or 750 kWh/day for a 10-hour operation
Manpower requirements	5 to 8 personnel
Space requirements	2,000 square meters

Initial Stock of the PNOC-DOE Operated LWMF

17





THANK YOU!

Dir. Raquel S. Hulganga [raquelh@doe.gov.ph]

